

VARIABLE FREQUENCY DRIVE

Bentec VARIABLE FREQUENCY DRIVE is an own-developed adjustable AC motor drive system for drilling machinery.

AVAILABLE POWER RANGE:

Up to 2 600 hp / 1 939 kW



UNIQUE FEATURES

- Bentec-own development
- Water or air-cooled compact system
- Available for onshore and offshore rigs
- Field-approved equipment
- Full load-tested
- Built-in cubicle solution
- Remote access available

TECHNICAL DATA

VARIABLE FREQUENCY DRIVE

The Bentec VARIABLE FREQUENCY DRIVE is a state-of-the-art converter technology developed for the special operational requirements on drilling units. Because it has been self-developed by Bentec, the VARIABLE FREQUENCY DRIVE provides an absolutely reliable system for drilling applications.

The Bentec VARIABLE FREQUENCY DRIVE can be combined with the Bentec AC motor to create a perfectly aligned configuration able to meet all high power drilling requirements on rigs. Moreover, the system can also be adjusted to work with different types of motors such as ABB, GEB 22, Reliance, etc.

All parameters of the Bentec VARIABLE FREQUENCY DRIVE can be accessed remotely. Therefore, in the event of a failure, a service engineer can access the Bentec VARIABLE FREQUENCY DRIVE for troubleshooting purposes. Each Bentec VARIABLE FREQUENCY DRIVE is full load-tested before installation.

The Bentec VARIABLE FREQUENCY DRIVE is available as a water or air-cooled version, and meets all the requirements for operating main drives – such as top drives, drawworks, mudpumps, rotary tables, etc. – on drilling rigs.

Bentec combines all of the experience it has gained from more than 30 years of developing and enhancing power electronic systems to offer a highly reliable and field-proven VARIABLE FREQUENCY DRIVE.

TECHNICAL DATA

Supply voltage:	600V / 690V
Supply frequency:	50 Hz / 60 Hz
Output voltage:	575V / 600V / 660V
Output current:	Up to 3600A

AVAILABLE OPTIONS

Remote access
Water / Air-cooled
Rectifier
Circuit breaker
Chiller unit
Power control room